The T-CABLE-3 is a Laboratory-quality shielded high speed USB 2.0 extension cable approved for use with the full range of Telemakus USB products.

The T-CABLE-3 is 3ft in length with type A Male and Female connectors allowing USB devices to be connected to a standard PC, USB port or USB HUB.

The T-CABLE-3 uses an overmolded boot to provide greater support to the USB device. This improves the alignment between cable and device, providing a more reliable connection.

The high retention force allows cables to be attached without additional support preventing the cable becoming loose or breaking connection due it own weight. This allows Telemakus USB devices to be attached wherever the user needs them.

If the application requires a greater distance between PC and the device, 2 or more cables can be connected together up to a total length of 15ft.









## T-CABLE-3 Rev A Mar 2011

Ordering information					
Model	Length (L)	PI Connector	P2 Connector		
T-CABLE-3	3 ft (nom)	A type Male	A type Female		

<b>S</b> pecifications			
Specification			
3 ft (nominal)			
4.7 mm			
AL Mylar Wrap			
Braid 16/4/0.10 TC 65% coverage			
28 AWG X2 twisted Pair (90ohms +/-15%)			
24 AWG			
24 AWG			
Gold Flash Plated			




SHIELD 1: AL MYLAR WRAP
SHIELD 2: BRAID,16/4/0.10TC,
65% COVERAGE

CONDUCTOR1:28AWG(7/0.12TC),X2
INSULATION1:HD-PE. ID: Ø0.90±0.05
WHITE,GREEN (TWISTED PAIR)

DRAIN:28AWG(7/0.12TC)
CONDUCTOR2:24AWG(7/0.20TC),X2
INSULATION1:SR-PVC. ID: Ø1.1±0.05
BLACK,RED

WIRING DIAGRAM RFD USB +5 Volt 1 USB +5 Volt WHITE DATA -– 2 DATA – DATA + GREEN \_ 3 DATA + 3 -BLACK USB -5 Ground4 -- 4 USB -5 Ground BRAID+DRAIN GEN > PAIR

P2



Outline Drawing (units mm)

Environmental Environmental					
Temperature Range	-40 to +55 degC				



Phone: 916 458 6346 Fax: 916 983 8713 Email: mail@telemakus.com www.telemakus.com Primary Business Address 13405 Folsom Blvd #502 Folsom CA,95630