

Wire Wound Chip Inductor Kits

P/N	Case EIA (Metric)	20 pieces of each value (nH)																	
0603CP-KIT	0603 (1608)	1.8	2.2	3.3	4.7	5.6	6.8	8.5	12	15	22	27	33	47	68	120	150	220	330
	Tolerance	±5%																	
0805CP-KIT	0805 (2012)	2.7	3.3	5.6	6.8	8.2	12	18	22	27	33	56	68	82	120	180	220	270	330
	Tolerance	±5%																	

Multi-Layer, High Q Chip Inductor Kits

P/N	Case EIA (Metric)	50 pieces of each value (nH)																		
TF060303-KIT	0201 (0603)	0.4	0.8	1.5	1.8	2.2	2.7	3.3	3.9	4.7	6.8	10	18	22	27	33	39	47	68	
	Tolerance	±0.2nH		±0.3nH								±5%								
TF100505-KIT	0402 (1005)	1.0	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	6.8	10	12	15	27	33	47	68	100	
	Tolerance	±0.3nH										±5%								
TF160808-KIT	0603 (1608)	1.2	1.8	2.2	2.7	3.3	3.9	4.7	6.8	10	22	33	39	47	68	100	120	180	220	
	Tolerance	±0.3nH								±5%										

MLCC, High Q Capacitor Kits

P/N	Case EIA(Metric)	50 pieces of each value (pF)																		
0402H-KIT	0402 (1005)	0.2	0.3	0.5	0.7	0.9	1	1.2	1.5	2	2.2	2.7	3	3.6	4.7	5.6	6.8	8.2	10	
	Tolerance	±0.1pF	±0.05pF	±0.1pF															±5%	
0603H-KIT	0603 (1608)	0.5	0.6	0.8	1	1.2	1.5	1.8	2.2	2.4	3.3	3.9	4.7	5.6	6.8	10	22	33	68	
	Tolerance	±0.1pF												±0.25pF		±5%				

MLCC, ULTRA High Q Capacitor Kits

P/N	Case EIA (Metric)	50 pieces of each value (pF)																		
0402M-KIT	0402 (1005)	0.2	0.3	0.5	0.7	0.9	1	1.2	1.5	2	2.2	2.7	3	3.9	4.7	5.6	6.8	8.2	10	
	Tolerance	±0.1pF	±0.05pF	±0.1pF														±0.25pF	±5%	
0603M-KIT	0603 (1608)	0.5	0.6	0.8	1	1.2	1.5	1.8	2.2	2.7	3.3	3.9	4.7	5.6	6.8	10	22	33	47	
	Tolerance	±0.1pF												±0.25pF		±5%				