

This specification describes a 100-ohm, 26 AWG, shielded and jacketed twisted pair cable.

CONDUCTOR

Material: Silver-coated Copper
Size: AWG 26
Construction: 7 x 34
OD(nom): .019"

INSULATION

Material: Extruded Expanded PTFE
OD(nom): .045"

DRAIN WIRE

Material: Silver-coated Copper
Size: AWG 26
Construction: 7 x 34
OD(nom): .019"

CABLE

Two(2) of the above insulated conductors are cabled with the drain wire.

SHIELD

Material: Aluminum/Polyester Tape (Aluminum Down)
OD(nom): .092"

JACKET

Material: Extruded FEP
OD(nom): .105"
Minimum Bend Radius: 1.05" (static)

ELECTRICAL CHARACTERISTICS

Differential Impedance: 100 ± 10 Ω
Capacitance(nom): 12 pF/ft

COLOR

White, Pink
Jacket: Black

All of the statements, illustrations, technical information and recommendations contained herein are based on tests & other information Carlisle Interconnect Technologies believes to be reliable, but the accuracy or the completeness thereof or the suitability of the product described herein for a particular application or use is not guaranteed & this disclaimer is made in lieu of all warranties either expressed or implied.

CARLISLE INTERCONNECT TECHNOLOGIES CONFIDENTIAL

This document, containing proprietary information, is strictly confidential and is not to be disclosed by any person without written consent.

CARLISLE INTERCONNECT TECHNOLOGIES
ST. AUGUSTINE, FL

Drawn by:	Rachel Cole	Date:	5/24/12
Approved by:	Sherry Condrey	Date:	5/24/12
Initial Release:	09/08/06		
Description:	100-OHM TWISTED PAIR		
Part Number:	BL726HT-T100	Cage Code	92607

B	05/24/12	Added static min bend radius
A	10/26/07	Changed insulation color from lt blue to pink
-	09/08/06	Initial Release